

SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

MaxiFlex® Comfort™ 34-925

Boja - Premaz	Kobaltno plava
Boja - Podstava	Svijetlosiva
Dizajn	¾ premaz
Premaz	NBR (nitril butadien guma)
Tekstura premaza	Mikro pjena
Podstava	Pamuk, Najlon, Spandeks
Broj patenta	EP 1 608 808
Debljina preko dlana (mm)	1.10



Dimenzije

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
A) Ukupna duljina rukavice (+/-5 mm)	195	205	220	225	235	240	245
B) Duljina zgloba (mm)	55	1	60	70	75	75	75
C) Širina zgloba (mm)	60	65	70	70	70	70	70
D) Širina dlana (mm)	82	90	94	98	102	104	106
Boja štepa	Plava	Crvena	Narančasta	Bijela	Žuta	Crna	Zelena

EN rezultati testiranja

	Tijelo za ocjenu sukladnosti	Rezultat/prolaz
EN ISO 21420:2020+A1:2024	TÜV Rheinland	
EN 388:2016 + A1:2018	TÜV Rheinland	3121A
EN 407:2020 Zaštita od topline	TÜV Rheinland	X1XXXX

Tipične vrijednosti performansi

EN ISO 21420: Opći zahtjevi - Dexterity	Razina 5
EN 388:2016 + A1:2018 - A. Otpornost na abraziju	≥ 2000 ciklusa
EN 388:2016 + A1:2018 - B. Otpornost na razrezivanje	≥ 1,2 indeks
EN 388:2016 + A1:2018 - C. Otpornost na kidanje	≥ 25 njutna
EN 388:2016 + A1:2018 - D. Otpornost na probijanje	≥ 20 njutna
EN 388:2016 + A1:2018 - E. Otpornost na razrezivanje ISO	≥ 2 njutna

SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

MaxiFlex® Comfort™ 34-925

HandCare®

Savez za zdravlje kože dermatološki akreditiran

U skladu s REACH-om

Sanitized®

OEKO-TEX® STANDARD 100

Perivo 40°C/104°F



Posebne značajke

Bez silikona

U skladu s FDA 21 CFR 177.2600

Kontakt s hranom (EU)

Pogodne za dodirni zaslon

~~SILICONE~~



Pakiranje

Pari po jednoj plastičnoj vrećici	12
Poly bags per carton	12
Komada u kartonskoj kutiji	144
Dimenzije kartonske kutije (mm)	500 x 295 x 270

Težina

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
Težina rukavica / par (+/-6 gram)	38	44	52	56	60	62	
Bruto težina (kg)	6.50	7.40	8.30	8.80	9.10	9.40	
Težina kutije (kg)	1.00	1.00	1.00	1.00	1.00	1.00	
Neto težina (kg)	5.50	6.40	7.30	7.80	8.10	8.40	

Datum izdavanja: 03/09/2026

