

PRODUKTDATAARK

MaxiCut® Ultra™ 52-6755F

Farge på belegg	Svart
Farge på fôr	Svart
Design	¾ belagt strikkes hanske
Belegg	NBR (Nitril butadien gummi)
Beleggtektur	Micro-skum
Fôr	Nylon, Polyester, UHMWPE, Spandex, Tungsten
Håndflatetykkelse (mm)	1.30



Dimensjoner

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
A) Total hanskelenge (+/-5 mm)	210	220	235	240	250	250	255
B) Håndleddslengde (mm)	60	65	65	75	70	70	75
C) Håndleddsbredde (mm)	72	76	80	82	85	85	90
D) Håndflatebredde (mm)	85	87	93	96	100	103	105
Farge på overlås	Blå	Rød	Oransje	Hvit	Gul	Svart	Grønn

EN-testresultater

	Varslet organ	Resultat/bestått
EN ISO 21420:2020+A1:2024	TÜV Rheinland	
EN 388:2016 + A1:2018	TÜV Rheinland	4X43F
EN 16350:2014	TÜV Rheinland	R _v < 1,0 x 10 ⁸ Ω.

Vanlige ytelsesverdier

EN ISO 21420: Generelle krav - Dexterity	Nivå 5
EN 388:2016 + A1:2018 - A. Nedslitingsmotstand	≥ 8000 Sykluser
EN 388:2016 + A1:2018 - B. Kuttmotstand	X
EN 388:2016 + A1:2018 - C. Riftmotstand	≥ 75 Newton
EN 388:2016 + A1:2018 - D. Punkturtmotstand	≥ 100 Newton
EN 388:2016 + A1:2018 - E. Kuttbestandighet i ISO-kategori	≥ 30 Newton

HandCare®

Dermatologisk godkjent av Skin Health Alliance

I samsvar med REACH

Sanitized®

OEKO-TEX® STANDARD 100

Vaskbar 40°C/104°F



PRODUKTDATAARK

MaxiCut® Ultra™ 52-6755F

Spesielle trekk

Berøringsskjerm- tilpasset

Fri for silikon

Antistatisk



SILICONE



Innpakning

Par per mangepakning	12
Poly bags per carton	6
Antall kartonger	72
Størrelse på kartong (mm)	500 x 295 x 200

Vekt

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
Hanskevekt/par (+/-6 gram)	47	50	56	60	64	68	70
Bruttovekt (kg)	4.30	4.60	5.00	5.30	5.60	5.80	6.00
Kartongvekt (kg)	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Nettovekt (kg)	3.30	3.60	4.00	4.30	4.60	4.80	5.00

Issue date: 03/09/2026

