

PRODUKTDATAARK

MaxiCut® Oil™ 34-470LP

Farge på belegg	Grå
Farge på fôr	Grå
Design	Håndflatebelagt strikket hanske
Belegg	NBR with Leather Pad
Beleggtekstur	Lærpute
Fôr	Nylon z włóknem szklanym, Włókno szklane, Nylon, Spandex
Patentnummer	EP 1 608 808
Håndflatetykkelse (mm)	2.50



Dimensjoner

	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
A) Total hanskelengde (+/-5 mm)	220	230	240	245	
B) Håndleddslengde (mm)	60	65	1	65	
C) Håndleddsbredde (mm)	78	80	80	85	
D) Håndflatebredde (mm)	94	105	108	115	
Farge på overlås	Oransje	Hvit	Gul	Svart	

EN-testresultater

	Varslet organ	Resultat/bestått
EN ISO 21420:2020+A1:2024	SATRA IRE	
EN 388:2016 + A1:2018	SATRA IRE	4444D

Vanlige ytelsesverdier

EN ISO 21420: Generelle krav - Dexterity	Nivå 4
EN 388:2016 + A1:2018 - A. Nedslitingsmotstand	≥ 8000 Sykluser
EN 388:2016 + A1:2018 - B. Kuttmotstand	≥ 10,0 pekefinger
EN 388:2016 + A1:2018 - C. Riftmotstand	≥ 75 Newton
EN 388:2016 + A1:2018 - D. Punkturtmotstand	≥ 150 Newton
EN 388:2016 + A1:2018 - E. Kuttbestandighet i ISO-kategori	≥ 15 Newton

HandCare®

Dermatologisk godkjent av Skin Health Alliance

I samsvar med REACH

Sanitized®

OEKO-TEX® STANDARD 100



STANDARD
100
08.BH.57867
Hohenstein HTTI
www.oeko-tex.com

PRODUKTDATAARK

MaxiCut® Oil™ 34-470LP

Innpakning

Par per mangepakning	12
Poly bags per carton	6
Antall kartonger	72
Størrelse på kartong (mm)	500 x 295 x 270

Vekt

	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
Hanskevekt/par (+/-6 gram)	86	100	108	115	
Bruttovekt (kg)	7.30	8.30	8.90	9.40	
Kartongvekt (kg)	1.00	1.00	1.00	1.00	
Nettovekt (kg)	6.30	7.30	7.90	8.40	

Issue date: 03/09/2026

