

# SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

## MaxiCut® Ultra™ 52-3745FY

|                           |                                    |
|---------------------------|------------------------------------|
| Boja - Premaz             | Žuta                               |
| Boja - Podstava           | Žuta                               |
| Dizajn                    | Premaz preko dlana                 |
| Premaz                    | NBR (nitril butadien guma)         |
| Tekstura premaza          | Mikro pjena                        |
| Podstava                  | Poliester, Spandeks, UHMWPE-staklo |
| Broj patenta              | EP 1 608 808                       |
| Debljina preko dlana (mm) | 1.40                               |



### Dimenzije

|                                      | 6 (XS) | 7 (S)  | 8 (M)      | 9 (L)  | 10 (XL) | 11 (2XL) | 12 (3XL) |
|--------------------------------------|--------|--------|------------|--------|---------|----------|----------|
| A) Ukupna duljina rukavice (+/-5 mm) | 200    | 205    | 220        | 230    | 235     | 240      | 245      |
| B) Duljina zgloba (mm)               | 60     | 65     | 70         | 70     | 75      | 80       | 82       |
| C) Širina zgloba (mm)                | 67     | 72     | 74         | 76     | 78      | 82       | 82       |
| D) Širina dlana (mm)                 | 82     | 86     | 92         | 98     | 100     | 102      | 104      |
| Boja štepa                           | Plava  | Crvena | Narančasta | Bijela | Žuta    | Crna     | Zelena   |

### EN rezultati testiranja

|                           | Tijelo za ocjenu sukladnosti | Rezultat/prolaz |
|---------------------------|------------------------------|-----------------|
| EN ISO 21420:2020+A1:2024 | TÜV Rheinland                |                 |
| EN 388:2016 + A1:2018     | TÜV Rheinland                | 4442C           |

### Tipične vrijednosti performansi

|                                                          |                |
|----------------------------------------------------------|----------------|
| EN ISO 21420: Opći zahtjevi - Dexterity                  | Razina 5       |
| EN 388:2016 + A1:2018 - A. Otpornost na abraziju         | ≥ 8000 ciklusa |
| EN 388:2016 + A1:2018 - B. Otpornost na razrezivanje     | ≥ 10,0 indeks  |
| EN 388:2016 + A1:2018 - C. Otpornost na kidanje          | ≥ 75 njutna    |
| EN 388:2016 + A1:2018 - D. Otpornost na probijanje       | ≥ 60 njutna    |
| EN 388:2016 + A1:2018 - E. Otpornost na razrezivanje ISO | ≥ 10 njutna    |

### HandCare®

Savez za zdravlje kože dermatološki akreditiran

U skladu s REACH-om

Sanitized®

OEKO-TEX® STANDARD 100

Perivo 40°C/104°F



# SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

## MaxiCut® Ultra™ 52-3745FY

### Posebne značajke

Bez silikona

Pogodne za dodirni zaslon

~~SILICONE~~



### Pakiranje

|                                   |                 |
|-----------------------------------|-----------------|
| Pari po jednoj plastičnoj vrećici | 12              |
| Poly bags per carton              | 6               |
| Komada u kartonskoj kutiji        | 72              |
| Dimenzije kartonske kutije (mm)   | 500 x 295 x 200 |

### Težina

|                                   | 6 (XS) | 7 (S) | 8 (M) | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|-----------------------------------|--------|-------|-------|-------|---------|----------|----------|
| Težina rukavica / par (+/-6 gram) | 42     | 46    | 54    | 58    | 60      | 64       | 64       |
| Bruto težina (kg)                 | 4.40   | 4.70  | 5.30  | 5.50  | 5.80    | 6.00     | 5.80     |
| Težina kutije (kg)                | 1.00   | 1.00  | 1.00  | 1.00  | 1.00    | 1.00     | 1.00     |
| Neto težina (kg)                  | 3.40   | 3.70  | 4.30  | 4.50  | 4.80    | 5.00     | 4.80     |

Datum izdavanja: 03/09/2026

