


SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

MaxiCut® Ultra™ 44-6755F

Boja - Premaz	Crna
Boja - Podstava	Crna
Dizajn	¾ premaz
Premaz	NBR (nitril butadien guma)
Tekstura premaza	Mikro pjena
Podstava	Najlon, Poliester, UHMWPE, Spandeks, Tungsten
Debljina preko dlana (mm)	1.30



Dimenzije

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
A) Ukupna duljina rukavice (+/-5 mm)	210	220	235	240	250	250	255
B) Duljina zgloba (mm)	60	65	65	75	70	70	75
C) Širina zgloba (mm)	72	76	80	82	85	85	90
D) Širina dlana (mm)	85	87	93	96	100	103	105
Boja štepa	Plava	Crvena	Narančasta	Bijela	Žuta	Crna	Zelena

EN rezultati testiranja

	Tijelo za ocjenu sukladnosti	Rezultat/prolaz
EN ISO 21420:2020+A1:2024	TÜV Rheinland	
EN 388:2016 + A1:2018	TÜV Rheinland	4X43F
EN 16350:2014	TÜV Rheinland	$R_v < 1,0 \times 10^8 \Omega$

Tipične vrijednosti performansi

EN ISO 21420: Opći zahtjevi - Dexterity	Razina 5
EN 388:2016 + A1:2018 - A. Otpornost na abraziju	≥ 8000 ciklusa
EN 388:2016 + A1:2018 - B. Otpornost na razrezivanje	X
EN 388:2016 + A1:2018 - C. Otpornost na kidanje	≥ 75 njutna
EN 388:2016 + A1:2018 - D. Otpornost na probijanje	≥ 100 njutna
EN 388:2016 + A1:2018 - E. Otpornost na razrezivanje ISO	≥ 30 njutna

SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

MaxiCut® Ultra™ 44-6755F

HandCare®

Savez za zdravlje kože dermatološki akreditiran

U skladu s REACH-om

Sanitized®

OEKO-TEX® STANDARD 100

Perivo 40°C/104°F



Posebne značajke

Pogodne za dodirni zaslon

Bez silikona

Kontakt s hranom (EU)

Anti statički



SILICONE



Pakiranje

Pari po jednoj plastičnoj vrećici	12
Poly bags per carton	6
Komada u kartonskoj kutiji	72
Dimenzije kartonske kutije (mm)	500 x 295 x 200

Težina

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
Težina rukavica / par (+/-6 gram)	47	50	56	60	64	68	70
Bruto težina (kg)	4.30	4.60	5.00	5.30	5.60	5.80	6.00
Težina kutije (kg)	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Neto težina (kg)	3.30	3.60	4.00	4.30	4.60	4.80	5.00

Datum izdavanja: 03/09/2026

