

# PRODUKTDATAARK

## MaxiCut® Ultra™ 52-4755D

|                        |                                                                    |
|------------------------|--------------------------------------------------------------------|
| Farge på belegg        | Svart                                                              |
| Farge på fôr           | Lysegrå                                                            |
| Design                 | ¾ belagt strikket hanske                                           |
| Belegg                 | NBR (Nitril butadien gummi)                                        |
| Beleggtekstur          | Micro-skum                                                         |
| Fôr                    | Nylon, Stainless-Steel, Polyester, UHMWPE, Spandex, Włókno szklane |
| Håndflatetykkelse (mm) | 1.10                                                               |



### Dimensjoner

|                                  | 6 (XS) | 7 (S) | 8 (M)   | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|----------------------------------|--------|-------|---------|-------|---------|----------|----------|
| A) Total hanskellengde (+/-5 mm) | 210    | 220   | 235     | 240   | 250     | 250      | 255      |
| B) Håndleddslengde (mm)          | 65     | 60    | 70      | 75    | 75      | 75       | 75       |
| C) Håndleddsbredde (mm)          | 80     | 78    | 82      | 83    | 85      | 88       | 90       |
| D) Håndflatebredde (mm)          | 85     | 90    | 96      | 100   | 102     | 105      | 107      |
| Farge på overlås                 | Blå    | Rød   | Oransje | Hvit  | Gul     | Svart    | Grønn    |

### EN-testresultater

|                           | Varslet organ | Resultat/bestått                          |
|---------------------------|---------------|-------------------------------------------|
| EN ISO 21420:2020+A1:2024 | TÜV Rheinland |                                           |
| EN 388:2016 + A1:2018     | TÜV Rheinland | 4X43D                                     |
| EN 16350:2014             | TÜV Rheinland | R <sub>v</sub> < 1,0 x 10 <sup>8</sup> Ω. |

### Vanlige ytelsesverdier

|                                                            |                 |
|------------------------------------------------------------|-----------------|
| EN 388:2016 + A1:2018 - A. Nedslitingsmotstand             | ≥ 8000 Sykluser |
| EN 388:2016 + A1:2018 - B. Kuttmotstand                    | X               |
| EN 388:2016 + A1:2018 - C. Riftmotstand                    | ≥ 75 Newton     |
| EN 388:2016 + A1:2018 - D. Punkturtmotstand                | ≥ 100 Newton    |
| EN 388:2016 + A1:2018 - E. Kuttbestandighet i ISO-kategori | ≥ 15 Newton     |
| EN ISO 21420: Generelle krav - Dexterity                   | Nivå 5          |

### HandCare®

Dermatologisk godkjent av Skin Health Alliance

I samsvar med REACH

Sanitized®

OEKO-TEX® STANDARD 100

Vaskbar 40°C/104°F



# PRODUKTDATAARK

## MaxiCut® Ultra™ 52-4755D

### Spesielle trekk

Berøringsskjerm- tilpasset

Fri for silikon

Antistatisk



**SILICONE**



### Innpakning

|                           |                 |
|---------------------------|-----------------|
| Par per mangepakning      | 12              |
| Poly bags per carton      | 6               |
| Antall kartonger          | 72              |
| Størrelse på kartong (mm) | 500 x 295 x 200 |

### Vekt

|                            | 6 (XS) | 7 (S) | 8 (M) | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|----------------------------|--------|-------|-------|-------|---------|----------|----------|
| Hanskevekt/par (+/-6 gram) | 45     | 46    | 56    | 60    | 63      | 67       | 71       |
| Bruttovekt (kg)            | 4.20   | 4.60  | 5.00  | 5.30  | 5.40    | 5.80     | 6.10     |
| Kartongvekt (kg)           | 1.00   | 1.00  | 1.00  | 1.00  | 1.00    | 1.00     | 1.00     |
| Nettovekt (kg)             | 3.20   | 3.60  | 4.00  | 4.30  | 4.40    | 4.80     | 5.10     |

Issue date: 03/09/2026

