


PRODUCT DATA SHEET

MaxiFlex® Cut™ 34-8453

Colour - Coating	Black
Colour - Liner	Green
Design	3/4 coated knitwrist
Coating	NBR (Nitrile Butadiene Rubber)
Coating texture	Micro-Foam for Controlled Grip
Liner	Polyester, Spandex, UHMWPE-Glass-Nylon
Patent number	EP 1 608 808
Palm thickness (mm)	0.90



Dimensions

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
A) Total glove length (+/- 5 mm)	205	220	230	235	245	250	255
B) Wrist length (mm)	64	64	1	70	72	74	72
C) Wrist width (mm)	68	70	72	74	74	76	78
D) Palm width (mm)	88	92	97	99	101	103	106
Overlock colour	Blue	Red	Orange	White	Yellow	Black	Grey

EN Test Results

	Notified body	Result/Pass
EN ISO 21420:2020+A1:2024	TÜV Rheinland	
EN 388:2016 + A1:2018	TÜV Rheinland	4331B

Typical Performance Values

EN ISO 21420:2020 - General requirements - Dexterity	Level 5
EN 388:2016 + A1:2018 - A. Abrasion Resistance	≥ 8000 Cycles
EN 388:2016 + A1:2018 - B. Cut Resistance	≥ 5,0 index
EN 388:2016 + A1:2018 - C. Tear Resistance	≥ 50 newtons
EN 388:2016 + A1:2018 - D. Puncture Resistance	≥ 20 newtons
EN 388:2016 + A1:2018 - E. Cut Resistance ISO	≥ 5 Newton

HandCare®

Skin Health Alliance Dermatologically Accredited

REACH compliant

Sanitized®

OEKO-TEX® STANDARD 100

Washable 40°C/104°F



PRODUCT DATA SHEET

MaxiFlex® Cut™ 34-8453

Special features

Touchscreen Compatible



Packaging

Pairs per poly bag	12
Poly bags per carton	6
Carton count	72
Carton dimensions (mm)	500 x 295 x 200

Weight

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
Glove weight / pair (+/- 6 gram)	36	40	42	46	48	50	56
Gross weight (kg)	3.75	4.00	4.30	4.50	4.65	4.80	5.00
Carton weight (kg)	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Net weight (kg)	2.75	3.00	3.30	3.50	3.65	3.80	4.00

Issue date: 03/09/2026

