

# PRODUKTDATAARK

## MaxiCut® Ultra™ 52-3745FY

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Farge på belegg        | Gul                                                     |
| Farge på fôr           | Gul                                                     |
| Design                 | Håndflatebelagt strikket hanske                         |
| Belegg                 | NBR (Nitril butadien gummi)                             |
| Beleggtekstur          | Micro-skum                                              |
| Fôr                    | Polyester, Spandex, Przędza UHMWPE-włókno szklane-nylon |
| Patentnummer           | EP 1 608 808                                            |
| Håndflatetykkelse (mm) | 1.40                                                    |



### Dimensjoner

|                                 | 6 (XS) | 7 (S) | 8 (M)   | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|---------------------------------|--------|-------|---------|-------|---------|----------|----------|
| A) Total hanskelengde (+/-5 mm) | 200    | 205   | 220     | 230   | 235     | 240      | 245      |
| B) Håndleddslengde (mm)         | 60     | 65    | 70      | 70    | 75      | 80       | 82       |
| C) Håndleddsbredde (mm)         | 67     | 72    | 74      | 76    | 78      | 82       | 82       |
| D) Håndflatebredde (mm)         | 82     | 86    | 92      | 98    | 100     | 102      | 104      |
| Farge på overlås                | Blå    | Rød   | Oransje | Hvit  | Gul     | Svart    | Grønn    |

### EN-testresultater

|                           | Varslet organ | Resultat/bestått |
|---------------------------|---------------|------------------|
| EN ISO 21420:2020+A1:2024 | TÜV Rheinland |                  |
| EN 388:2016 + A1:2018     | TÜV Rheinland | 4442C            |

### Vanlige ytelsesverdier

|                                                            |                   |
|------------------------------------------------------------|-------------------|
| EN ISO 21420: Generelle krav - Dexterity                   | Nivå 5            |
| EN 388:2016 + A1:2018 - A. Nedslitingsmotstand             | ≥ 8000 Sykluser   |
| EN 388:2016 + A1:2018 - B. Kuttmotstand                    | ≥ 10,0 pekefinger |
| EN 388:2016 + A1:2018 - C. Riftmotstand                    | ≥ 75 Newton       |
| EN 388:2016 + A1:2018 - D. Punkturtmotstand                | ≥ 60 Newton       |
| EN 388:2016 + A1:2018 - E. Kuttbestandighet i ISO-kategori | ≥ 10 Newton       |

### HandCare®

Dermatologisk godkjent av Skin Health Alliance

I samsvar med REACH

Sanitized®

OEKO-TEX® STANDARD 100

Vaskbar 40°C/104°F



STANDARD  
100  
08.BH.57867  
Hohenstein HTTI  
www.oeko-tex.com

# PRODUKTDATAARK

## MaxiCut® Ultra™ 52-3745FY

### Spesielle trekk

Fri for silikon

Berøringsskjerm- tilpasset

**SILICONE**



### Innpakning

|                           |                 |
|---------------------------|-----------------|
| Par per mangepakning      | 12              |
| Poly bags per carton      | 6               |
| Antall kartonger          | 72              |
| Størrelse på kartong (mm) | 500 x 295 x 200 |

### Vekt

|                            | 6 (XS) | 7 (S) | 8 (M) | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|----------------------------|--------|-------|-------|-------|---------|----------|----------|
| Hanskevekt/par (+/-6 gram) | 42     | 46    | 54    | 58    | 60      | 64       | 64       |
| Bruttovekt (kg)            | 4.40   | 4.70  | 5.30  | 5.50  | 5.80    | 6.00     | 5.80     |
| Kartongvekt (kg)           | 1.00   | 1.00  | 1.00  | 1.00  | 1.00    | 1.00     | 1.00     |
| Nettovekt (kg)             | 3.40   | 3.70  | 4.30  | 4.50  | 4.80    | 5.00     | 4.80     |

Issue date: 03/09/2026

