

PRODUCT DATA SHEET

MaxiCut® Ultra™ 52-5755E

Colour - Coating	Black
Colour - Liner	Grey
Design	¾ coated knitwrist
Coating	NBR (Nitrile Butadiene Rubber)
Coating texture	Micro-Foam for Controlled Grip
Liner	Nylon, Stainless-Steel, Polyester, UHMWPE, Spandex, Glass
Palm thickness (mm)	1.20



Dimensions

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
A) Total glove length (+/- 5 mm)	210	220	235	240	250	250	255
B) Wrist length (mm)	65	70	70	70	72	75	75
C) Wrist width (mm)	80	82	85	86	87	90	92
D) Palm width (mm)	87	88	95	98	102	105	105
Overlock colour	Blue	Red	Orange	White	Yellow	Black	Green

EN Test Results

	Notified body	Result/Pass
EN ISO 21420:2020+A1:2024	TÜV Rheinland	
EN 388:2016 + A1:2018	TÜV Rheinland	4X43E
EN 16350:2014	TÜV Rheinland	R _v < 1,0 x 10 ⁸ Ω.

Typical Performance Values

EN ISO 21420:2020 - General requirements - Dexterity	Level 5
EN 388:2016 + A1:2018 - A. Abrasion Resistance	≥ 8000 Cycles
EN 388:2016 + A1:2018 - B. Cut Resistance	X
EN 388:2016 + A1:2018 - C. Tear Resistance	≥ 75 newtons
EN 388:2016 + A1:2018 - D. Puncture Resistance	≥ 100 newtons
EN 388:2016 + A1:2018 - E. Cut Resistance ISO	≥ 22 Newton

HandCare®

Skin Health Alliance Dermatologically Accredited

REACH compliant

Sanitized®

OEKO-TEX® STANDARD 100

Washable 40°C/104°F



PRODUCT DATA SHEET

MaxiCut® Ultra™ 52-5755E

Special features

Touchscreen Compatible

Silicone free

Antistatic



~~SILICONE~~



Packaging

Pairs per poly bag	12
Poly bags per carton	6
Carton count	72
Carton dimensions (mm)	500 x 295 x 200

Weight

	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)
Glove weight / pair (+/- 6 gram)	50	53	61	63	67	70	74
Gross weight (kg)	4.60	4.80	5.30	5.50	5.80	6.00	6.30
Carton weight (kg)	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Net weight (kg)	3.60	3.80	4.30	4.50	4.80	5.00	5.30

Issue date: 03/09/2026

