


# PRODUCT DATA SHEET

## MaxiCut® Ultra™ 44-5745E

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| Colour - Coating    | Black                                                     |
| Colour - Liner      | Grey                                                      |
| Design              | Palm coated knitwrist                                     |
| Coating             | NBR (Nitrile Butadiene Rubber)                            |
| Coating texture     | Micro-Foam for Controlled Grip                            |
| Liner               | Nylon, Stainless-Steel, Polyester, UHMWPE, Spandex, Glass |
| Palm thickness (mm) | 1.20                                                      |



### Dimensions

|                                  | 6 (XS) | 7 (S) | 8 (M)  | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|----------------------------------|--------|-------|--------|-------|---------|----------|----------|
| A) Total glove length (+/- 5 mm) | 210    | 220   | 235    | 240   | 250     | 250      | 255      |
| B) Wrist length (mm)             | 65     | 70    | 70     | 70    | 72      | 75       | 75       |
| C) Wrist width (mm)              | 80     | 82    | 85     | 86    | 87      | 90       | 92       |
| D) Palm width (mm)               | 87     | 88    | 95     | 98    | 102     | 105      | 105      |
| Overlock colour                  | Blue   | Red   | Orange | White | Yellow  | Black    | Green    |

### EN Test Results

|                           | Notified body | Result/Pass                               |
|---------------------------|---------------|-------------------------------------------|
| EN ISO 21420:2020+A1:2024 | TÜV Rheinland |                                           |
| EN 388:2016 + A1:2018     | TÜV Rheinland | 4X43E                                     |
| EN 16350:2014             | TÜV Rheinland | R <sub>v</sub> < 1,0 x 10 <sup>8</sup> Ω. |

### Typical Performance Values

|                                                      |               |
|------------------------------------------------------|---------------|
| EN ISO 21420:2020 - General requirements - Dexterity | Level 5       |
| EN 388:2016 + A1:2018 - A. Abrasion Resistance       | ≥ 8000 Cycles |
| EN 388:2016 + A1:2018 - B. Cut Resistance            | X             |
| EN 388:2016 + A1:2018 - C. Tear Resistance           | ≥ 75 newtons  |
| EN 388:2016 + A1:2018 - D. Puncture Resistance       | ≥ 100 newtons |
| EN 388:2016 + A1:2018 - E. Cut Resistance ISO        | ≥ 22 Newton   |

### HandCare®

Skin Health Alliance Dermatologically Accredited

REACH compliant

Sanitized®

OEKO-TEX® STANDARD 100

Washable 40°C/104°F



# PRODUCT DATA SHEET

## MaxiCut® Ultra™ 44-5745E

### Special features

Antistatic

Touchscreen Compatible

Silicone free

Food contact (EU)



**SILICONE**



### Packaging

|                        |                 |
|------------------------|-----------------|
| Pairs per poly bag     | 12              |
| Poly bags per carton   | 6               |
| Carton count           | 72              |
| Carton dimensions (mm) | 500 x 295 x 200 |

### Weight

|                                  | 6 (XS) | 7 (S) | 8 (M) | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|----------------------------------|--------|-------|-------|-------|---------|----------|----------|
| Glove weight / pair (+/- 6 gram) | 50     | 53    | 61    | 63    | 67      | 70       | 74       |
| Gross weight (kg)                | 4.60   | 4.80  | 5.30  | 5.50  | 5.80    | 6.00     | 6.30     |
| Carton weight (kg)               | 1.00   | 1.00  | 1.00  | 1.00  | 1.00    | 1.00     | 1.00     |
| Net weight (kg)                  | 3.60   | 3.80  | 4.30  | 4.50  | 4.80    | 5.00     | 5.30     |

Issue date: 03/09/2026

