

SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

MaxiCut® Ultra™ with AD-APT® 52-6745F



| | |
|---------------------------|---|
| Boja – Premaz | Crna |
| Boja – Podstava | Crna |
| Dizajn | Premaz preko dlana |
| Premaz | NBR (nitril butadien guma) |
| Tekstura premaza | Mikro pjena |
| Podstava | Najlon, Poliester, UHMWPE, Spandeks, Tungsten |
| Debljina preko dlana (mm) | 1.30 |



Dimenzije

| Raspon veličina | Veličina 6 (XS) | Veličina 7 (S) | Veličina 8 (M) | Veličina 9 (L) | Veličina 10 (XL) | Veličina 11 (XXL) | Veličina 12 (XXXL) |
|-----------------------------------|-----------------|----------------|----------------|----------------|------------------|-------------------|--------------------|
| Ukupna duljina rukavice (+/-5 mm) | 210 | 220 | 235 | 240 | 250 | 250 | 255 |
| Duljina zgloba (mm) | 60 | 65 | 65 | 75 | 70 | 70 | 75 |
| Širina zgloba (mm) | 72 | 76 | 80 | 82 | 85 | 85 | 90 |
| Širina dlana (mm) | 85 | 87 | 93 | 96 | 100 | 103 | 105 |
| Boja štepa | Plava | Crvena | Narančasta | Bijela | Žuta | Crna | Zelena |

EN rezultati testiranja

| Test | Tijelo za ocjenu sukladnosti | Rezultat/prolaz |
|---------------------------|------------------------------|--|
| EN ISO 21420:2020+A1:2024 | TÜV Rheinland | Da |
| EN 388:2016 + A1:2018 | TÜV Rheinland | 4X43F |
| EN 16350:2014 | TÜV Rheinland | Vertical resistance $R_v < 1,0 \times 10^8 \Omega$. |

SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

MaxiCut® Ultra™ with AD-APT® 52-6745F

Tipične vrijednosti performansi

| | |
|--|---|
| EN ISO 21420: Opći zahtjevi Dexterity | Razina 5 |
| EN 388:2016 + A1:2018 A. Otpornost na abraziju | > 8000 ciklusa |
| EN 388:2016 + A1:2018 B. Otpornost na razrezivanje | Mehaničke opasnosti |
| | <ul style="list-style-type: none">A: Otpornost na habanje - broj trljanja (Razina 0-4)B: Otpornost na posjekotine - Coupe Test - Indeks (Razina 0-5)C: Otpornost na trganje - N (razina 0-4)D: otpornost na probijanje N (razina 0-4)E: TDM otpornost na rezove prema ISO 13997 - N (razina A-F)*F: Zaštita od udaraca prema EN 13594:2015 - Da/N (P=Da) |
| | <i>* Rezultati testa Coupe samo su indikativni, dok je ispitivanje otpornosti TDM (ISO13997) referentni rezultat funkcionalnosti.</i> |
| EN 388:2016 + A1:2018 C. Otpornost na kidanje | > 75 njutna |
| EN 388:2016 + A1:2018 D. Otpornost na probijanje | > 100 njutna |
| EN 388:2016 + A1:2018 E. Otpornost na razrezivanje ISO | ≥ 30 njutna |

HandCare®

| | |
|--|---------------|
| Dermatološki akreditirano od Skin Health Alliance | Da |
| REACH compliant | Da |
| OEKO-TEX® Standard 100 - 08.BH.57867 Hohenstein HTTI | Certificirano |
| Perivo | 40°C/104°F |
| Sanitized® | Da |



Posebne značajke

| | |
|---------------------------|----|
| Pogodne za dodirni zaslon | Da |
| Bez silikona | Da |
| Anti statički | Da |



SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

MaxiCut® Ultra™ with AD-APT® 52-6745F

Pakiranje

| | |
|---|-----------------|
| Pari po jednoj plastičnoj vrećici | 12 |
| Plastičnih vrećica po kartonskoj kutiji | 6 |
| Komada u kartonskoj kutiji | 72 |
| Dimenzije kartonske kutije (mm) | 500 x 295 x 200 |

Težina

| Raspon veličina | Veličina 6 (XS) | Veličina 7 (S) | Veličina 8 (M) | Veličina 9 (L) | Veličina 10 (XL) | Veličina 11 (XXL) | Veličina 12 (XXXL) |
|-----------------------------------|-----------------|----------------|----------------|----------------|------------------|-------------------|--------------------|
| Težina rukavica / par (+/-6 gram) | 47 | 50 | 56 | 60 | 64 | 68 | 70 |
| Bruto težina (kg) | 4.3 | 4.6 | 5 | 5.3 | 5.6 | 5.8 | 6 |
| Težina kutije (kg) | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Neto težina (kg) | 3.3 | 3.6 | 4.0 | 4.3 | 4.6 | 4.8 | 5.0 |

Datum izdavanja: 06/03/2026

