

# SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

## MaxiCut® Ultra™ 44-6745F



Boja – Premaz	Crna
Boja – Podstava	Crna
Dizajn	Premaz preko dlana
Premaz	NBR (nitril butadien guma)
Tekstura premaza	Mikro pjena
Podstava	Najlon, Poliester, UHMWPE, Spandeks, Tungsten
Debljina preko dlana (mm)	1.30



### Dimenzije

Raspon veličina	Veličina 6 (XS)	Veličina 7 (S)	Veličina 8 (M)	Veličina 9 (L)	Veličina 10 (XL)	Veličina 11 (XXL)	Veličina 12 (XXXL)
Ukupna duljina rukavice (+/-5 mm)	210	220	235	240	250	250	255
Duljina zgloba (mm)	60	65	65	75	70	70	75
Širina zgloba (mm)	72	76	80	82	85	85	90
Širina dlana (mm)	85	87	93	96	100	103	105
Boja štepa	Plava	Crvena	Narančasta	Bijela	Žuta	Crna	Zelena

### EN rezultati testiranja

Test	Tijelo za ocjenu sukladnosti	Rezultat/prolaz
EN ISO 21420:2020+A1:2024	TÜV Rheinland	Da
EN 388:2016 + A1:2018	TÜV Rheinland	4X43F
EN 16350:2014	TÜV Rheinland	Vertical resistance $R_v < 1,0 \times 10^8 \Omega$ .

# SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

## MaxiCut® Ultra™ 44-6745F

### Tipične vrijednosti performansi

EN ISO 21420: Opći zahtjevi Dexterity	Razina 5
EN 388:2016 + A1:2018 A. Otpornost na abraziju	> 8000 ciklusa
EN 388:2016 + A1:2018 B. Otpornost na razrezivanje	Mehaničke opasnosti
	<ul style="list-style-type: none"><li>A: Otpornost na habanje - broj trljanja (Razina 0-4)</li><li>B: Otpornost na posjekotine - Coupe Test - Indeks (Razina 0-5)</li><li>C: Otpornost na trganje - N (razina 0-4)</li><li>D: otpornost na probijanje N (razina 0-4)</li><li>E: TDM otpornost na rezove prema ISO 13997 - N (razina A-F)*</li><li>F: Zaštita od udaraca prema EN 13594:2015 - Da/N (P=Da)</li></ul>
	<i>* Rezultati testa Coupe samo su indikativni, dok je ispitivanje otpornosti TDM (ISO13997) referentni rezultat funkcionalnosti.</i>
EN 388:2016 + A1:2018 C. Otpornost na kidanje	> 75 njutna
EN 388:2016 + A1:2018 D. Otpornost na probijanje	> 100 njutna
EN 388:2016 + A1:2018 E. Otpornost na razrezivanje ISO	≥ 30 njutna

### HandCare®

Dermatološki akreditirano od Skin Health Alliance	Da
REACH compliant	Da
OEKO-TEX® Standard 100 - 08.BH.57867 Hohenstein HTTI	Certificirano
Perivo	40°C/104°F
Sanitized®	Da



### Posebne značajke

Pogodne za dodirni zaslon	Da
Bez silikona	Da
Kontakt s hranom (EU)	Da
Anti statički	Da



# SIGURNOSNO TEHNIČKI LIST ZA PROIZVOD

## MaxiCut® Ultra™ 44-6745F

### Pakiranje

Pari po jednoj plastičnoj vrećici	12
Plastičnih vrećica po kartonskoj kutiji	6
Komada u kartonskoj kutiji	72
Dimenzije kartonske kutije (mm)	500 x 295 x 200

### Težina

Raspon veličina	Veličina 6 (XS)	Veličina 7 (S)	Veličina 8 (M)	Veličina 9 (L)	Veličina 10 (XL)	Veličina 11 (XXL)	Veličina 12 (XXXL)
Težina rukavica / par (+/-6 gram)	47	50	56	60	64	68	70
Bruto težina (kg)	4.3	4.6	5	5.3	5.6	5.8	6
Težina kutije (kg)	1	1	1	1	1	1	1
Neto težina (kg)	3.3	3.6	4.0	4.3	4.6	4.8	5.0

Datum izdavanja: 06/03/2026

